Monogram.

ZTD910BF/SF/WF – GE Monogram 30" Warming Drawer

Single Oven Installation (in inches)



Warming Drawer Dimensions (in inches)



Double Oven Installation (in inches)



Note: Additional clearance between cutouts may be required. Check to be sure that oven supports above the Warming Drawer location do not obstruct the required interior 23-1/2" depth and 9-1/4" height.

Listed by
Underwriters
Laboratories

For answers to your Monogram,® GE Profile™ or GE appliance questions, visit our website at GEAppliances.com or call GE Answer Center® service, 800.626.2000.

Specification Revised 10/05
130716

Monogram.

ZTD910BF/SF/WF – GE Monogram 30" Warming Drawer

Undercounter Installation (in inches)



Note: When installing warming drawer with a cooktop, allow a 2" minimum from cooktop burner box bottom to top of cut-out.

Important Installation Note:
Must provide anti-tip brace at the back of the cabinet and at the top of the cutout.

Optional Accessories:

ZXD30B – 3/4" wood panel trim kit

***Note:** When installing the warming drawer below a cooktop, a solid barrier must be installed at 1" from the lowest point of the bottom of cooktop burner box to the top of cutout. Use any solid material such as 1/4" thick plywood. Allow at least 1/4" air gap between the barrier and the top of the warming drawer. See label on top of the warming drawer for approved cooktop models.

- When installed, the front face of the drawer will be nearly flush with adjacent cabinetry doors.
- Drawer overlaps will conceal cut edges on all sides of the opening. The rough opening for the drawer must be:
  –Depth 23-1/2" min. from inside back to front of cabinet frame.
  –Width 25-1/2" for 27" wide models, 28-1/2" for 30" wide models.
  –Height 9-1/4"
- 5" min. above floor or 1" above toekick. 23-1/4" from floor to bottom of cutout is recommended for under countertop installation.

Installation below a cooktop:
Warming drawers are approved for installation below only certain specified cooktop models. See the label attached to the top of the warming drawer for approved models. A solid barrier and air gap between cooktop and warming drawer is required. See Note above.

Installation below a cabinet drawer:
The warming drawer may be installed beneath a cabinet drawer. In this installation, a solid barrier should be installed above the warming drawer to block access. Use any solid material such as 1/4" thick plywood. Allow at least 1/4" air gap between the barrier and the top of the warming drawer. Observe the 5" min. above the floor or 1" above the toekick minimum installation height.

Note: If you are installing in frameless cabinets, it may be necessary to install 1/2" wide cleats to accept drawer mounting screws. See drawer to find exact locations of mounting screws.

Specification Revised 10/05
130716

Side to Side Installation:
Install two warming drawers in separate cutouts. Allow 2" min. between cutouts.



Side to Side Installation

Listed by Underwriters Laboratories

For answers to your Monogram,® GE Profile™ or GE appliance questions, visit our website at GEAppliances.com or call GE Answer Center® service, 800.626.2000.

Monogram.

ZTD910BF/SF/WF – GE Monogram 30" Warming Drawer



Features and Benefits

- 1.92 cu. ft. Capacity
- Variable Temperature Control – Proof (80)/ Low (140)/Med (170)/High (210)
- Variable Humidity Control – Crisp to Moist
- Half Rack
- "On" Signal Light
- On/Off Rocker Switch
- Removable Stainless Steel Pan
- Full Extension Ball Bearing Glides
- Hidden Controls Provide Flush Installation Appearance
- Variable Installation Options
- Pan Set Included
- Model ZTD910WFWW – White on white
- Model ZTD910BFBB – Black on black
- Model ZTD910SFSS – Stainless steel

Specification Revised 10/05
130716